



H05V-K / H07V-K (NYAF) 60227 IEC02

PVC İZOLELİ, BÜKÜLGEN, TEK DAMARLI TEŞİSAT KABLOLARI
PVC INSULATED, SINGLE CORE CABLES WITH FLEXIBLE COPPER CONDUCTOR



TECHNICAL DATA SHEET



STANDARTLAR

STANDARDS

TS EN 50525-2-31
BS EN 50525-2-31
DIN EN 50525-2-31
IEC 60227-3

UK CODE

2491X/6491X

SERTİFİKALAR CERTIFICATES



YAPISI / CONSTRUCTION

TEKNİK ÖZELLİKLER / SPECIFICATIONS

İletken / conductor

1  İnce Çok Telli Bakır
Fine-stranded copper
(Class 5) EN 60228

 Min. bükülme yarı çapı
Min. bending radius
D<8 ise 4xD
8<D<12 ise 5xD
D>12 ise 6xD

 160° Max. kısa devre sıcaklığı
Max. short circuit
temperature

izole / insulation

2  PVC Polivinil klorür
Polyvinyl chloride

 70° Max. çalışma sıcaklığı
Max. operating temperature

 300/500 V
450/750 V Beyan gerilimi U₀/U
Rated voltage U₀/U

 +5°C Min. Çalışma Sıcaklığı
Minimum operating temperature

 2 kV/2.5 kV Deney gerilimi
AC test voltage

 Tek kablo düşey alev yayılma testi
Flame propagation test on single cable -
EN 60332-1

UYGULAMA ALANLARI / APPLICATIONS



Hareketli tesislerde ve cihazlarda, kapalı ve kuru yerlerde, panolarda kullanılır

Used in closed and dry areas, switch and distribution boards, and also used for moving installations and equipments



PVC İZOLELİ, BÜKÜLGEN, TEK DAMARLITE Sİ SAT KABLoları
PVC INSULATED, SINGLE CORE CABLES WITH FLEXIBLE COPPER CONDUCTOR

STANDARTLAR
STANDARDS
TS EN 50525-2-31
BS EN 50525-2-31
DIN EN 50525-2-31
IEC 60227-3

SERTİFİKALAR CERTIFICATES



Cu/PVC

H05V-K ürünü için sahip olunan tek belge TSE

RoHS'a uygundur
RoHS Compliant